



Floor-Standing Model 2500.FS

FEATURES AND BENEFITS

RECESSED, ELECTRONIC SPIGOT

Fast-flow, electronic dispensing, with recessed lighted spout for sanitary activation.

ACCU-TEMP

Serves water at the perfect temperature every time.

SANITATION-IN-PLACE (SIP®)

Enhanced in-tank self-sanitization system programmed to clean reservoir and waterways automatically for low maintenance.

ADVANCED BRITA® FILTRATION SYSTEM

1,500-gallon (5678 L) capacity with superior certifications for great-tasting water. The 1 micron filter uses activated coconut carbon block to reduce chlorine (taste and odor) and lead, and removes 99.99% of cysts.*

CERTIFICATION

Unit is certified by CSA to NSF/ANSI 42, 53, 61 and 372. Compliant to California Health and Safety Code (AB 1953). All components are UL listed.

DURABLE BUILD

440 stainless steel water reservoir and a dual mechanical float system.

SAFETY FUNCTION

Dual operation safety activation lock function for hot water safety.

SUSTAINABLE ALTERNATIVE

This Brita® Hydration Station® can reduce as many as 11,300 bottles each year.**



By Haws Corporation® • www.BritaHydrationStation.com • Call Haws at 1.888.909.4297

*Substances reduced may not be in all user's water. **Standard 16.9 oz. bottles, based on 3,000 gallons per year with average usage. The BRITA trademark and logo are registered trademarks of Brita LP and are used under license by Haws Corporation®. All rights reserved.



Floor-Standing Model 2500.FS

DIMENSIONS

Size: 11.7" w x 15" d x 43.5" h (29.7 cm x 38.1 cm x 110.5 cm)

Dispensing Area: 6.25" w x 2.5" d x 9.75" h
(15.9 cm x 6.35 cm x 24.8 cm)

Flow Rate: 1.26 - 1.52 oz/sec



By Haws Corporation® • www.BritaHydrationStation.com • Call Haws at 1.888.909.4297

The BRITA trademark and logo are registered trademarks of Brita LP and are used under license by Haws Corporation®. All rights reserved.