

model 8317LT

Area Light

FEATURES & BENEFITS

OPTIONS

For more information, visit www.hawsco.com or call (888) 640-4297.



SPECIFICATIONS

Model 8317LT is a vapor tight and gasketed green light for continuous illumination of the 8317CTFP series showers. Model is CSA electrical certified, TYPE 4. For Class 1, Div. 2, Group B, C & D. Temperature Code: T2C; only when used with 8317CTFP.

APPLICATIONS

Model is QPS-C-US Certified, TYPE 4. For Class 1, Div. 2, Group B, C & D. Temperature Code: T2C; only when used with 8317CTFP.



NOTES: (CONTINUED FROM SHEET 1)

2 LIGHT BULB REPLACEMENT INSTRUCTIONS:

- 1) REMOVE GUARD AND GLOBE:
 FIRST LOOSEN SET SCREW (LOCATED ON GUARD WHERE SHOWN). NEXT, ROTATE GUARD COUNTER CLOCKWISE UNTIL GUARD IS FREE. FINALLY ROTATE GLOBE COUNTER CLOCKWISE UNTIL GLOBE IS FREE AND LAMP IS EXPOSED.
- 2) REPLACE LAMP WITH HAWS P/N 0003225495.
 WARNING EXPLOSION HAZARD SUBSTITUTION OF
 COMPONENTS MAY IMPAIR SUITABILITY FOR CLASS 1,
 DIVISION 2.
- 3) REPLACE GUARD AND GLOBE:
 ROTATE GLOBE CLOCKWISE ONTO THREADS UNTIL SEALED
 AGAINST GASKET. NEXT, ROTATE GUARD CLOCKWISE
 ONTO THREADS UNTIL TIGHT. FINALLY TIGHTEN SET SCREW.
- 4) WARNING: WHEN INSTALLED ON 8317CTFP, THE ASSEMBLY IS ONLY RATED FOR T2C.
- 5) ALL INSTALLATIONS MUST BE INSTALLED IN COMPLIANCE WITH LOCAL, STATE, AND/OR FEDERAL CODES.

