

FEATURES & BENEFITS

HAWS ORIGINAL

Designed and assembled with domestic and foreign parts in the US by Haws.

BYPASS

Best-in-class cold water bypass flow (65% of rated tempered water flow) means continued protection under adverse conditions.

POSITIVE SHUT OFF

Actively suspends hot water flow when cold water supply is lost to protect against scalding.

PRESSURE DROP

Lowest internal pressure drop for this valve class – essential where supply pressure is low.

TEMPERATURE MANAGEMENT

Paraffin-based thermal actuation technology keeps outlet temperature within tight specifications to prevent scalding and hypothermia.

SHUTTLE DESIGN

Superior shuttle design combined with premium material selection eliminates valve binding and reduces maintenance costs.

MIXING CHAMBER

Innovative funnel design generates turbulent flow to ensure consistent temperature blending across entire flow range.

DEPOSITS RESISTANT

Lime and calcium resistant materials used throughout prevent valve sticking and provide a long service life.

FLOW RATES

Flow range of 1 to 31 GPM (117.3 L) provides service for one emergency combination shower or multiple eyewashes, reducing complexity and hardware costs.

LEAD FREE

Certified to NSF61 and California Health and Safety Code 116875 (AB 1953-2006).

ANTI-SCALD PROTECTION

Redundant anti-scald protection with internal cold water bypass ensures reliable protection. Main tempering valve provides primary protection while backup shutoff valve provides secondary high-temp protection. Internal cold water bypass supplies cold water if hot water supply or main tempering valve fails.

EXTENDED WARRANTY

3-year extended warranty based on superior engineering and best-in-class material selection.



SPECIFICATIONS

Model 9201H - Thermostatic Mixing Valve (patent pending)

	MAXIMUM		MINIMUM	
Flow Rate	31 GPM	117.3 LPM	1 GPM	4 LPM
Hot Inlet Temperature	180° F	82° C	120° F	49° C
Recommended Hot Inlet Temperature	140° F	60° C		
Cold Inlet Temperature	70° F	21° C	40° F	4° C
Adjustable Outlet Temperature Range	90° F	32° C	60° F	16° C
Operating Pressure	125 PSI	8.6 BAR		
Factory Temperature Set Point	85° F	29° C		
Cold Water Bypass	20 GPM	75.7 LPM @ 30 PSID		



Inlet Ports: 1" NPT(f) Outlet Port: 1-1/4" NPT(F)

Maximum Inlet Pressure Differential: +/- 10%

Listings: ASSE 1071, ANSI Z358.1, CSA B125.3, NSF/ANSI 61-section 8, NSF/ANSI 372, California Health and Safety Code 116875 (AB 1953-2006).

FLOW CAPACITIES

MODEL	INLET	OUTLET	MINIMUM FLOW	INTERNAL COLD WATER BY-PASS AT 30PSI DROP	PRESSURE DROP							
9201H	1"	1-1/4"			5	10	15	20	30	45	60	PSI
					.345	.689	1.03	1.38	2.07	3.10	4.13	BAR
			1	20	13	18	22	25	31	38	44	GPM
			4	76	49	68	83	95	117	144	167	L/MIN



1455 KLEPPE LANE
SPARKS, NEVADA 89431
(775) 359-4712 FAX (775) 359-7424
E-MAIL: HAWS@HAWSCO.COM
WEBSITE: WWW.HAWSCO.COM

ECN NO. 4405	REVISED PER BY: WVC	MODEL(S) 9201H	PART NUMBER 0002080235.D
DRAWN: WVC	DATE: 12/10/03	INSTALLATION	DRAWING NO. 16054A
APPROVED: [Signature]	SCALE: 1:4	DRAWING TYPE: INSTALLATION	SHEET 1 OF 1