

## FEATURES & BENEFITS

### CONSTRUCTION

Superior strength and durability are achieved with the use of 12 gauge Type 304 Stainless Steel, along with integral 3/8" (.95 cm) thick cast stainless bowls. The unit is trimmed with a glossy green powder-coat finish and it is secured to the ground with an integral mounting plate.

### DRAIN CLEAN-OUT

Top-down access to the drain allows the fountain portion to be cleaned without taking the unit apart, good for outdoor settings with drain-clogging sediment such as leaves, garbage, and other debris.

### ACCESSIBILITY

Ease of maintenance is achieved with the use of an extra-large access door supplied with heavy-duty door hinges, and is locked by square key pins.

### BUBBLER HEADS

Polished chrome-plated brass bubbler heads with integral basin shank for added strength. Shielded, angled stream opening provides a steady, sanitary source of drinking water at .45 gpm.

### DRINKING FOUNTAIN VALVES

The push-button activated valve offers the only all stainless steel valve body that is machined out of solid bar stock, is fully serviceable through the front of the push button assembly offering access to the water control cartridge and integral water supply strainer, and with front access to the water stream height adjustment for easy maintenance without having to remove the valve. Operating pressure range of 30 to 90 psi (2.1 to 6.2 bar).

### VANDAL-RESISTANT

The bubbler heads, push buttons, drain strainers and access plates are locked in place, discouraging unwanted vandal tampering.



## SPECIFICATIONS

Model 3500 superior-duty ADA vandal-resistant pedestal drinking fountain shall include a 12 gauge Type 304 Stainless Steel pedestal with integral 3/8" (.95 cm) thick cast stainless steel basins, all powder-coated green, push-button operated stainless steel valves with front-accessible cartridge and flow adjustment, 100% lead free waterways, polished chrome-plated brass vandal-resistant bubbler heads, polished chrome-plated brass vandal-resistant waste strainers with top-down clean-out access, large access door with heavy duty hinges and square key locks, vandal-resistant bottom plate, integral mounting plate, and 1-1/2" slip waste. In extreme environments related to heat and cold, product(s) must be protected from damage/exposure due to these extreme conditions.

## APPLICATIONS

This unique drinking fountain is the perfect addition to parks, rest areas, and correctional facilities where vandalism may be more prone to take place. By welding the bowls directly to the upright, they become one with the unit, preventing removal. That, in addition to many other vandal-resistance features, makes this fountain virtually indestructible. This series fountain may also be applicable in a wide assortment of other places not mentioned due to its great appeal through its vandal proof and wheelchair accessible design. Model meets all current Federal Regulations for the disabled including those in the Americans with Disabilities Act. Haws manufactures drinking fountains, faucets and electric water coolers to be lead-free by all known definitions including NSF/ANSI/CAN 61- Section 9, NSF/ANSI/ CAN 372, California Proposition 65, and the Federal Safe Drinking Water Act. Product is compliant to California Health and Safety Code 116875 (AB 1953-2006), and 116876 (AB 100) "NSF/ANSI/CAN 61: Q ≤ 1".

## OPTIONS

- Mounting Plate: Model MTG.3500 mounting plate gives in-ground support for the 3500 series pedestal fountains and includes the mounting hardware.
- Mounting System: Model MTG.3501, galvanized steel anchors.
- Sand Trap: Model 6635, in-pedestal sand trap for models 3500, 3511 and 3600 series fountains.
- Sand Trap: Model 6611, sand trap for installing adjacent to pedestal drinking fountains to help prevent debris and contaminants from clogging waste line.

For more information, visit [www.hawscow.com](http://www.hawscow.com) or call (888) 640-4297.



- 
- Technical drawing of the Pet Fountain Model MTG.3500, showing side and top views with dimensions and callouts.
- Side View Dimensions:**
- Overall height: 28-1/2" (724mm)
  - Top section height: 41-1/2" (1054mm)
  - Base section height: 18" (457mm)
  - Base width: 34" (864mm)
  - Base depth: 35-1/2" (902mm)
  - Base to spout outlet distance: 27" (686mm)
  - Base to spout outlet distance (to spout outlet): 34" (864mm)
  - Base to spout outlet distance (to spout outlet): 35-1/2" (902mm)
- Top View Dimensions:**
- Overall width: 7" (178mm MIN.)
  - Overall depth: 178mm MIN.
- Callouts and Components:**
- 1: 1-1/2" O.D. TAILPIECE
  - 2: 3/8" O.D. CONNECTOR (MODEL 3500 ONLY)
  - 3: 1-1/2" SLIP PVC
  - 4: 3/8" O.D. TUBING SUPPLIED (NOT SUPPLIED ON MODEL 3500)
  - 5: 1/2" NPT SCREWDRIVER STOP (NOT SUPPLIED) ADJUST LOCATION AS NEEDED WHEN INSTALLING PET FOUNTAIN MODEL.
  - 6: 30" SQUARE CONCRETE SLAB (NOT SUPPLIED)
  - 7: MODEL MTG.3501 (OPTIONAL) OR MODEL MTG.3500 (OPTIONAL)
  - 8: WASTE (NOT SUPPLIED)
  - 9: 1/2" IPS FROM SHUT-OFF (NOT SUPPLIED)

1455 KLEPPE LANE  
SPARKS, NEVADA 89431  
(775) 359-4712 FAX (775) 359-7424  
E-MAIL: [HAWS@HAWSCO.COM](mailto:HAWS@HAWSCO.COM)  
WEBSITE: [WWW.HAWSCO.COM](http://WWW.HAWSCO.COM)

ECON NO.		REVISED PER BY:		MODEL(S)	
DRAWN:		ECON: 5998		FV	
DATE:		CHKD:		3500/3500D	
F. VASQUEZ (02-04-99)		JC		REVISION	
APPROVED:		DATE:		SCALE: 1:13	
FV		04/17/24		DRAWING TYPE	
				INSTALLATION	
				SIZE: A	
				SHEET 1 OF 2	
				17	